



Essential for a worry-free journey. The ContiTireSealant.

- › Replacement product of original equipment quality “Engineered in Germany”
- › Non-hazardous latex-based tyre sealant
- › Extended shelf life of up to five years
- › This squeeze bottle can be used as a replacement for similar products from other manufacturers
- › Sealant bottle can be disposed of in the household waste
- › Usage with any standard compressor for tyre puncture sealing



www.continental-mobility.com



Part number: 17120380000

Extended movability in case of a puncture.

ContiTireSealant restores mobility in case of punctures - quickly and safely. The tyre sealant is transferred with a squeeze bottle into the tyre. The tyre can then be inflated again with any standard compressor for tyre puncture sealing, enabling the onward journey to the nearest garage or tyre service (max. 80 km/h and max. 200 km). ContiTireSealant seals passenger car tyre punctures caused by nails or similar objects with a diameter of up to 6 mm.

Product contents:

- > 600 ml squeeze bottle
- > User manual
- > Plastic gloves
- > Nozzle
- > Small bag with valve core remover, valve core and speed warning label

Technical specifications of sealant bottle:

Sealant amount	Shelf life	Dimensions
600 ml	5 years	Ø 86 mm × 150 mm
Weight	Application temperature	
640 g	-30°C to +60°C	

Application for passenger car tyres:

The product can be used for the tyre dimensions which are shown in the following chart and with a required tyre pressure of up to 300 kPa (3 bar, 43 psi).

Tyre width in mm	Tyre cross section	Rim size in inches
130 195	25-80	R 10 R 14
135/	25 30 35 40 45 50 55 60 65 70 75 80	R 15
145/	25 30 35 40 45 50 55 60 65 70 75 80	
155/	25 30 35 40 45 50 55 60 65 70 75 80	
165/	25 30 35 40 45 50 55 60 65 70 75 80	
175/	25 30 35 40 45 50 55 60 65 70 75 80	
185/	25 30 35 40 45 50 55 60 65 70 75 80	
195/	25 30 35 40 45 50 55 60 65 70 75 80	
205/	25 30 35 40 45 50 55 60 65 70 75 80	
215/	25 30 35 40 45 50 55 60 65 70 75 80	
225/	25 30 35 40 45 50 55 60 65 70 75	
235/	25 30 35 40 45 50 55 60 65 70 75	R 16
245/	25 30 35 40 45 50 55 60 65 70	
155/	25 30 35 40 45 50 55 60 65 70 75 80	
165/	25 30 35 40 45 50 55 60 65 70 75 80	
175/	25 30 35 40 45 50 55 60 65 70 75 80	
185/	25 30 35 40 45 50 55 60 65 70 75 80	
195/	25 30 35 40 45 50 55 60 65 70 75 80	
205/	25 30 35 40 45 50 55 60 65 70 75	
215/	25 30 35 40 45 50 55 60 65 70 75	
225/	25 30 35 40 45 50 55 60 65 70 75	
235/	25 30 35 40 45 50 55 60 65 70 75	R 17
245/	25 30 35 40 45 50 55 60 65 70 75	
185/	25 30 35 40 45 50 55 60 65 70 75 80	
195/	25 30 35 40 45 50 55 60 65 70 75 80	
205/	25 30 35 40 45 50 55 60 65 70 75	
215/	25 30 35 40 45 50 55 60 65 70 75	
225/	25 30 35 40 45 50 55 60 65 70 75	
235/	25 30 35 40 45 50 55 60 65 70 75	
245/	25 30 35 40 45 50 55 60 65 70 75	
255/	25 30 35 40 45 50 55 60 65 70 75	
265/	25 30 35 40 45 50 55 60 65 70	
275/	25 30 35 40 45 50 55 60 65	
285/	25 30 35 40 45 50 55 60 65	

Tyre width in mm	Tyre cross section	Rim size in inches
205/	25 30 35 40 45 50 55 60 65 70	R 18
215/	25 30 35 40 45 50 55 60 65 70	
225/	25 30 35 40 45 50 55 60 65 70	
235/	25 30 35 40 45 50 55 60 65 70	
245/	25 30 35 40 45 50 55 60 65 70	
255/	25 30 35 40 45 50 55 60 65 70	
265/	25 30 35 40 45 50 55 60 65 70	
275/	25 30 35 40 45 50 55 60 65	
285/	25 30 35 40 45 50 55 60	
295/	25 30 35 40 45 50 55	
305/	25 30 35 40 45	R 19
315/	25 30 35	
215/	25 30 35 40 45 50 55 60 65	
225/	25 30 35 40 45 50 55 60 65	
235/	25 30 35 40 45 50 55 60 65	
245/	25 30 35 40 45 50 55 60 65	
255/	25 30 35 40 45 50 55 60 65	
265/	25 30 35 40 45 50 55 60	
275/	25 30 35 40 45 50 55	
285/	25 30 35 40 45 50	
295/	25 30 35 40 45	R 20
305/	25 30 35 40	
315/	25 30 35	
225/	25 30 35 40 45 50 55 60	
235/	25 30 35 40 45 50 55 60	
245/	25 30 35 40 45 50 55 60	
255/	25 30 35 40 45 50 55 60	
265/	25 30 35 40 45 50 55 60	
275/	25 30 35 40 45 50 55	
285/	25 30 35 40 45 50	
295/	25 30 35 40 45	R 21
305/	25 30 35 40	
245/	25 30 35 40 45 50 55	
255/	25 30 35 40 45 50 55	
265/	25 30 35 40 45 50 55	
275/	25 30 35 40 45 50	
285/	25 30 35 40 45	
295/	25 30 35 40	
305/	25 30 35	
315/	25 30	
325/	25 30	

Last updated: 02/2016